

Patent claims

Add
QA

- 5 1. An arrangement for eliminating, or at least for reducing the size of, interspaces between a first and a second element and between the second element and a third element, all three elements being arranged one behind the other, along a common longitudinal axis, at the distal arrangement end and being rotatable relative to one another about the relevant longitudinal axis, the three
10 elements being formed, in particular, by a suture-feed part, a suture-clamping part and a suture-accommodating part of an arrangement for guiding at least two sutures through a wall, in particular of an artery of an individual, in the vicinity of the edge region of an
15 opening provided therein, it being the case that the first element, provided at the distal arrangement end, is connected, via an inner sleeve, to a first retaining or rotary adjustment part provided at the proximal arrangement end, it being the case that the second
20 element, directly adjacent to the first element provided at the distal arrangement end, is connected to an outer sleeve, which encloses the abovementioned inner sleeve and is connected to a second retaining or rotary adjustment part, provided at a distance from the abovementioned first
25 retaining or rotary adjustment part in the direction of the distal arrangement end, and it being the case that the third element, directly adjacent to the abovementioned second element at the distal arrangement end in the direction of the proximal arrangement end, is connected to
30 a third retaining or rotary adjustment part, which is adjacent to the abovementioned second retaining or rotary adjustment part in the direction of the distal arrangement end, characterized in that in each case one spring device (13, 14) is provided between the first retaining or rotary
35 adjustment part (35) and the second retaining or rotary adjustment part (34) and between the second retaining or

retaining or rotary adjustment parts (34, 36) coupled to one another in the direction of the abovementioned longitudinal axis, the outer sleeve (7), which is connected to the second retaining or rotary adjustment part (34), can be displaced relative to said second retaining or rotary adjustment part (34) in the direction of the abovementioned longitudinal axis and at its proximal end, which is located between the first and second retaining or rotary adjustment parts (35, 34), has an edge (17), in each case one spring device (18, 19) being provided between said edge and the respectively adjacent sides of the first and second retaining or rotary adjustment parts (35, 34).

3. The arrangement as claimed in claim 1, characterized in that the respective spring device (13, 14, 18, 19) is formed by a compression spring.

4. The arrangement as claimed in claim 2, characterized in that the respective spring device (13, 14, 18, 19) is formed by a compression spring.